

MATERIAL SAFETY DATA SHEET

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

- Product name: DSC BLUE DEVIL
- **Product Description:** Water base cleaner
- Manufacturer: Deep South Chemical, Inc.
 - 229 Millstone Road

Broussard, LA 70518 (337) 837-9931

- For Emergency: Call CHEMTREC 1-800-424-9300 Outside the U.S.A. (703)-527-3887
- Contact Person: Glenn Ray
- Formula: Proprietary
- MSDS Revised: January 1, 2014

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

			PEL(OSHA)	TLV(ACGIH)	
Hazardous components	CAS Number	%	TWA STEL	TWA STEL	IDLH
Sodium Metasilicate, Anhydrous	6834-92-3	1-4	N/E N/E	N/E N/E	N/E
Sulfuric Acid	7664-93-9	0.0025	1mg/m ³ N/E	$1 mg/m^3 3 mg/m^3$	15 mg/m^3
Poly(oxy-1,2-ethanediyl), alpha-(nonylpehnyl)- omega-hydroxy-	9016-45-9	2-5	N/E N/E	N/E N/E	N/E
Sodium Hypochlorite	7681-52-9	2-3	N/E N/E	N/E N/E	N/E
Sodium Hydroxide	1310-73-2).4-0.6	N/E 2mg/m ³ (Ceiling)	N/E 2mg/m ³ (Ceiling)	10mg/m ³
Available Chlorine	7782-50-5	2-3	0.5ppm 1.0ppm	0.5ppm 1.0ppm	10ppm

Note: This product may contain trace amounts (<1ppm) of ethylene oxide CAS Number 75-21-8.

SECTION 3. HAZARDS IDENTIFICATION, INCLUDING EMERGENCY OVERVIEW

Effects of overexposure

Inhalation: This product may cause irritation to nose, throat, and respiratory tract **Skin Contact:** This product may cause irritation to the skin. Defatting of the skin can occur with frequent or long-term skin contact.

Eye Contact: Irritation to eyes.

Ingestion: There may be irritation of the mouth, throat, and digestive tract.



SECTION 4. FIRST AID MEASURES

- **Eyes:** Move victim away from exposure and into fresh air. If irritation persists, seek medical attention. For direct exposure, flush with clean water for 15 minutes. Hold eyelids apart to ensure flushing of the entire eye surface.
- **Inhalation:** Move victim away from source of exposure and into fresh air. If irritation persists, seek medical attention. If victim is not breathing, artificial respiration should be administered.
- **Skin:** Remove contaminated clothes. Cleanse affected area thoroughly with soap and water. If irritation persists, seek medical attention. Wash contaminated clothing.
- **Ingestion:** Do not induce vomiting or give anything by mouth. Drink plenty of water. Seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Fire fighting measures

Extinguishing Media: Product will not burn. **Decomposition/Combustion Products:** N/A **Special Fire Fighting Procedures:** N/A

Explosive Properties:

LEL: N/D UEL: N/D

SECTION 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Use proper personal protective equipment. Stay upwind and away from spill. If spill is indoors, ventilate area. Keep out of drains, sewers or waterways. Use sand or other inert material to contain and soak up spill.

Waste disposal method: Dispose of according to local, state and federal regulations in an approved disposal facility or recycling facility.

SECTION 7. HANDLING AND STORAGE

Storage: Store in a well-ventilated area. Keep container tightly closed when not in use. Store in cool, dry area.

Handling: Use proper personal protective equipment. Avoid contact with skin or eyes. Avoid breathing of vapors. Handle in well-ventilated workspace. When handling do not eat or drink.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Keep work area well ventilated.

Protective clothing: Impermeable gloves and impervious clothing as appropriate.

Eye protection: Chemical goggles where splashing may occur.

Respiratory Protection: Use appropriate respiratory protection when handling or in case of insufficient ventilation.

Special Protection: Safety shower, eye bath, and washing facilities should be available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Specific gravity @ 75°F(H₂O = 1): 1.11 Flash Point(PMCC Method)(°F): N/A Vapor density (Air = 1): N/D Solubility: Soluble in water. Vapor pressure @ 75: 1.0 mmHg Evaporation Rate: <1 Appearance: Clear blue liquid. Odor: Mild bleach smell. Boiling Point(°F): >212 pH: 12.0-13.0 Auto-ignition: N/D

SECTION 10. STABILITY AND REACTIVITY

Stability and Reactivity: Stable in normal conditions.
Incompatible Materials: Ammonia and acids.
Hazardous Decomposition Products: Smoke, carbon oxides, chlorine.
Hazardous Polymerization: None described.

SECTION 11. TOXICOLOGICAL INFORMATION

Hazardous Ingredients: Irritating to eyes and skin. Immediate Health Effects: Irritation. Delayed Health Effects: Defatting of skin with frequent or prolonged skin contact.

SECTION 12. ECOLOGICAL INFORMATION

Persistence and Degradability: All the components are biodegradable.
Biodegradation: N/D

ErC50 (72 hours) Skeletonema costatum: N/D
LC50 (48 hours) Acartia tonsa: N/D
LC50 (10 days) Corophium voliotator: N/D

Aquatic Toxicity: 96 HR LC50 (mysid shrimp) N/D
Oil and grease content in slurry(Polymer 2 LB/BBL): N/D

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal: If spilled, dispose according to local regulations. Recycle waste containers and clean out residues.

SECTION 14. TRANSPORT INFORMATION

DOT Transport Information: UN 1791, Hypochlorite Solutions, 8, PG III

Shipping Label: Corrosive



SEC

SECTION 15. REGULATORY INFORMATION

Toxic Substances Control Act (TCSA): All ingredients are on the TSCA inventory or are not required to be listed on the TSCA inventory.

)
Component	CERCLA RQ (lbs)
Ethylene Oxide	10
Sulfuric Acid	1000
Sodium Hypochlorite	100
Sodium Hydroxide	1000
Chlorine	10
SARA 302 Components-40 CF	R 355 Appendix A
Component	TPQ (Threshold Planning Quantity) (I
Ethylene Oxide	1000
0.10 1	
Sulfuric Acid	1000
Chlorine	1000 100
	100 40 CFR 370.2
Chlorine Section 311/312 Hazard Class- Immediate (X) Delayed () Fire () Reactive (X)	100 40 CFR 370.2
Chlorine Section 311/312 Hazard Class- Immediate (X) Delayed () Fire () Reactive (X) Sudden Release of Pressu	100 40 CFR 370.2

NFPA RATING: Health (2) Fire (0) Reactivity (1)

The trace amounts of **ethylene oxide** (**EO**) in this product are not expected to result in either acute or long-term hazards when the material is handled in accordance with sections 7 & 8. You should be aware though, that EO is a cancer and reproductive hazard. Repeated exposure to ethylene oxide may be harmful. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1ppm for an eight-hour time weighted average exposure. The ethylene oxide standard (29 CFR 1910.1047) regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with the OSHA ethylene oxide standard.

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATION OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE ON IN COMBINATION WITH OTHER PRODUCTS. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY AND SUITABILITY OF EACH PRODUCT OR PRODUCT COMBINATION FOR THEIR OWN PURPOSES. UNLESS OTHERWISE OBTAINED IN WRITING, WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM HANDLING AND USE OF OUR PRODUCTS, WHETHER USED ALONE OR IN COMBINATION WITH OTHER PRODUCTS.

N/D= No data; N/A = Not available; N/E= Not established