



TECHNICAL DATA SHEET
April 1, 2011

KO 1200
Hydrogen Sulfide Scavenger

Description:

KO 1200 is a liquid, water soluble zinc chelate designed to scavenge H₂S in most brine and fresh water drilling fluid systems. It also provides some degree of protection against corrosion resulting from oxygen. Being a liquid, it can be injected directly into the mud pump suction line with a chemical pump, thus avoiding costly and messy mixing of powders.

KO 1200 is compatible with all brine and fresh water polymer systems, all brine and fresh systems free of solids, brine water clay and starch systems, and weighted systems where additional dispersion is not a problem.

Application:

Drilling fluids should be pretreated with **KO 1200** prior to drilling a formation suspected of containing hydrogen sulfide. One 55 gallon drum per thousand barrels of drilling fluid is recommended initially to scavenge up to 50-80 PPM soluble sulfide. Moderate H₂S intrusions can be controlled by a daily continuous treatment of 7-12 gallons of **KO 1200** through a chemical pump at the mud pump suction. Treatment of higher-volume intrusions require the injection of correspondingly larger quantities of **KO 1200**.

Shipping And Handling Instructions:

KO 1200 is available in 55 gallon drums. A Material Safety Data Sheet outlining recommended safe handling of **KO 1200** is available upon request.