

## **TECHNICAL DATA SHEET** April 1, 2011

# LX 200 Gas Check Cement DSC Cement Gas Control-Latex **Additive**

Fluid Loss Agent

LX 200 Gas Check Cement Additive is an aqueous based Latex polymer that is blended into the mix water prior to preparation of the cement slurry. LX 200 Gas Check Additive has a mild-retarding effect when used alone at BHCT < 125°F. Depending on the cement type and the thickening time desired, LX 200 Gas Check Cement Additive may require the use of an accelerator at low temperatures or at low densities when mixed with fresh water. The recommended accelerator is sodium silicate. The fluid loss control performance of LX 200 Gas Check Cement Additive is improved when used in conjunction with dispersants and most retarders. The use of dispersant alone is sufficient to provide retardation up to about 150°F BHCT. Typically, the addition of a retarder is required above 150°F.

### **Application Areas**

- All API classes of cement
- Freshwater, or seawater slurries

#### **Typical Range of Use**

Temperature	70°F - 200°F (21°C - 93-3°C) BHCT
Concentration	0.5 - 2.5 US GALLONS / 94 LB SACK
Density	12 - 20 lb/US gal (1.44 - 2.4 g/cm <sup>3</sup> )

#### **Physical Properties**

- Latex Polymer
- Specific gravity =  $1.00 \text{ g/cm}^3$
- Disperses in water

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. DSC does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of the information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as federal, state or local laws which may be encountered in the use thereof. Such questions should be investigated by the user.